



# HAND HELD AUXILIARY HYDRAULICS



For CAT 416/420/430 D, E & F Series

## Features

Allows precise control of hydraulic flow to match the needs of each hand held hydraulic work tool. There's no longer a need to haul around expensive stand alone hydraulic power units.

Six position standard flow selector locks in flow at 3, 5, 7, 9, 12 or 15 gpm and is quickly and easily adjusted. Adjustable relief to custom tailor the system to your work tools. The optional high flow kit features flow settings at 8, 13, 18, 22, 26 or 30 gpm.

### Additional Options Available



Quick Couplers



Hose Reel



## 6 Position Adjustable Flow Control

## Specifications

Low Flow (std):	3, 5, 7, 9, 12 or 15 gpm
High Flow (opt):	8, 13, 18, 22, 26 or 30 gpm
Pressure (Adjustable):	250 - 3,000 psi
Factory Set Pressure:	2,100 psi

## Benefits

**Roads and Bridges:** Allows use of hand held breakers, diamond chainsaws, chipping hammers, tampers for compacting soil and hand held core drills for taking core sample or installing re-bar.

**Municipalities and Rental Yards:** Allows use of additional hand held work tools such as earth augers, trash pumps, post drivers, digging spades, cut-off saws, tree trimmers, impact wrenches, drills and crimping tools.

CK2535 - Standard Flow      CK2530 - High Flow      02/14