



HIGH PERFORMANCE HYDRAULICS & PTO KIT



For CAT Industrial Loaders

HYDRO PTO

30 gpm 3,300 psi 45 hp

Patent Pending

Specifications

Relief Pressure:	3,300 psi
Flow - Sized for PTO:	30 gpm
Adjustable Flow Settings at QDs:	8, 13, 18, 22, 26, 30 gpm
Theoretical Gross Hydraulic HP:	57.7 hhp
High Flow Quick Disconnects:	3/4 in. ISO
PTO Attachment Types:	540 rpm, 45 hp or less

Features

Operate pull-behind 540 rpm PTO attachments or hydraulically driven attachments in line with the three point hitch.

3/4 inch quick disconnects and controls are easily accessible for hydraulic pull-behind attachments and hand tools.

6 position flow selector for auxiliary hydraulic attachments and tools with settings at 8, 13, 18, 22, 26 and 30 gpm.



The CT820 kit includes the valve and all plumbing including QD's, wire harnesses, electric shut-off safety relay and brackets.

The CT870 kit includes the CT820 hydraulic kit, PTO motor and all necessary mounting hardware and hoses.

Benefits

CAT industrial loader owners can now operate any 540 rpm PTO attachment requiring 45 hp or less.

PTO attachments are typically less expensive and require less maintenance than hydraulically driven attachments.

A wider variety of larger hydraulic attachments (including hand tools) can be used due to the CT800 series kit increasing the flow available from the standard 9 gpm to 30 gpm.

Flow rate is easily adjusted with the 6 position selector knob and a selector lever to switch from auxiliary hydraulics to PTO.

05/09