



MINI COMPACTION PLATE DC5500 SERIES





Dual counterweights — By utilizing dual counterweight technology, the Coneqtec compaction line provides true vertical compaction force while eliminating the harmful horizontal vibration. This allows higher compaction forces to be used on smaller units without increasing the wear and tear on the rubber mounts or on the loader arms and compact utility loader.

Isolation mounts — The DC5500 series compaction plate utilizes four heavy duty isolation mounts that eliminate the vibration from being transferred back to the loader.

Specifications

MODEL	DC5500	DC5500	DC5500
Width (In)	41	52	60
Vertical Force (lbs)	5500	5500	5500
Frequency (VPM)	1900	1900	1900
Hydraulic Flow (GPM)	8 Min.	8 Min.	8 Min.
Operating Pressure (PSI)	1500	1500	1500
Base Plate Dimension (In)	41x18	52x18	60x18
Weight (lbs)	519	520	620

NOTES: All units are equipped with flow control valves to control flow to GPM to ensure correct VPM and force.

Extended front lip — This patented feature allows the DC5500 series to operate as a blade for leveling prior to compaction of the surface. The exclusive front lip design also gathers and levels the fill during the compaction operation.

Heavy duty construction — Heavy duty vibration isolators and thick steel construction allow the DC5500 to perform both as a compaction plate and a backfill blade.

Componetized construction — Vibratory unit is lubricated by a continuous oil bath. This results in longer life of the unit. The componetized construction allows easy removal should service or inspection ever be required.



Applications

Flat work — Level and compact sand or fill prior to pouring concrete floors or pads inside or out.

Landscaping — Level and compact fill around new construction sites. Level and compact slopes and areas disturbed by landscaping projects.

Driveways — Move sand or fill on site with loader, then attach DC5500 to level and compact prior to pouring concrete driveways or to laying asphalt driveways.

Compact recycled asphalt — Make quick work of recycled asphalt leveling and compaction in drives, parking areas and equipment areas.

Sold & Serviced By

P.O. BOX 9102 • WICHITA, KS 67277 • (888) 832-3462 • Fax (316) 946-5552